



Canadian Bioinformatics Workshops

www.bioinformatics.ca

This page is available in the following languages:

Afrikaans বাংলাৰাখী Català Dansk Deutsch Ελληνικά English English (CA) English (GB) English (US) Esperanto
Castellano Castellano (AR) Español (CL) Castellano (CO) Español (Ecuador) Castellano (MX) Castellano (PE)
Euskara Suomi français français (CA) Galego עברית hrvatski Magyar Italiano 日本語 한국어 Macedonian Malayu
Nederlands Norsk Sesotho sa Leboa polski Português română slovenski jezik српски srpski (latinica) Sotho svenska
中文 華語 (台灣) isiZulu



Attribution-Share Alike 2.5 Canada

You are free:



to Share — to copy, distribute and transmit the work



to Remix — to adapt the work



Under the following conditions:



Attribution. You must attribute the work in the manner specified by the author or licensor (but not in any way that suggests that they endorse you or your use of the work).



Share Alike. If you alter, transform, or build upon this work, you may distribute the resulting work only under the same or similar licence to this one.

- For any reuse or distribution, you must make clear to others the licence terms of this work.
- Any of the above conditions can be waived if you get permission from the copyright holder.
- The author's moral rights are retained in this licence.


[Disclaimer](#)

Your fair dealing and other rights are in no way affected by the above.

This is a human-readable summary of the Legal Code (the full licence) available in the following languages:
[English](#) [French](#)

Introduction to IGV The Integrative Genomics Viewer

Malachi Griffith, Obi Griffith, Jason Walker
Informatics for RNA-seq analysis
June 16 - 17, 2016



Visualization Tools in Genomics

- there are **over 40 different genome browsers**, which to use?
- depends on
 - task at hand
 - kind and size of data
 - data privacy

HT-seq Genome Browsers



Integrative
Genome
Viewer



UCSC
Genome Browser
Cancer Genome Browser



Trackster
(part of Galaxy)



Savant
Genome
Browser


- task at hand : visualizing HT-seq reads, especially good for inspecting variants
- kind and size of data : large BAM files, stored locally or remotely
- data privacy : run on the desktop, can keep all data private
- UCSC Genome Browser has been retro-fitted to display BAM files
- Trackster is a genome browser that can perform visual analytics on small windows of the genome, deploy full analysis with Galaxy

Integrative Genomics Viewer (IGV)


Desktop application for the interactive visual exploration of integrated genomic datasets




Epigenomics




Microarrays



NGS alignments



RNA-Seq



mRNA, CNV, Seq

<http://www.broadinstitute.org/igv>


>85,000 registrations (2014)

Features

With IGV you can...

- Explore large genomic datasets with an intuitive, easy-to-use interface.
- Integrate multiple data types with clinical and other sample information.
- View data from multiple sources:
 - local, remote, and “cloud-based”.
- Automation of specific tasks using command-line interface

IGV data sources






- View **local** files without uploading.
- View **remote** files without downloading the whole dataset.

Using IGV: the basics

- Launch IGV
- Select a reference genome
- Load data
- Navigate through the data
 - WGS data
 - SNVs
 - structural variations

Launch IGV



Launch IGV

Human hg18 All Go

1. Select genome from the drop-down menu



2. Load data

RefSeq genes

115M of 183M


Load data

Select File > Load from Server...




Open the Tutorials menu, select UI Basics

Screen layout



Screen layout




File formats and track types


- The **file format** defines the track type.
- The **track type** determines the display options
 - [BAM](#)
 - [BED](#)
 - [BedGraph](#)
 - [bigBed](#)
 - [bigWig](#)
 - [Birdsuite Files](#)
 - [CBS](#)
 - [CN](#)
 - [Cufflinks Files](#)
 - [Custom File Formats](#)
 - [Cytoband](#)
 - [FASTA](#)
 - [GCT](#)
 - [genePred](#)
 - [GFF](#)
 - [GISTIC](#)
 - [Goby](#)
 - [GWAS](#)
 - [IGV](#)
 - [LOH](#)
 - [MAF](#)
 - [Merged BAM File \(.bam.list\)](#)
 - [MUT](#)
 - [PSL](#)
 - [RES](#)
 - [SAM](#)
 - [Sample Information](#)
 - [SEG](#)
 - [SNP](#)
 - [TAB](#)
 - [TDF](#)
 - [Track Line](#)
 - [Type Line](#)
 - [VCF](#)
 - [WIG](#)
- For current list see: www.broadinstitute.org/igv/FileFormats

Viewing alignments

Whole chromosome view



Viewing alignments – Zoom in




How far do you need to zoom in to see the alignments?


30 kb or set a different threshold in Preferences

- Higher value → requires more memory
- Low coverage files → ok to use higher value
- Very deep coverage files → use lower value

Viewing alignments – Zoom in




Bases that do not match the reference sequence are highlighted by color



SNVs and Structural variations

- Important metrics for evaluating the validity of SNVs:
 - Coverage
 - Amount of support
 - Strand bias / PCR artifacts
 - Mapping qualities
 - Base qualities
- Important metrics for evaluating SVs:
 - Coverage
 - Insert size
 - Read pair orientation

Viewing SNPs and SNVs



Viewing SNPs and SNVs



Viewing Structural Events


- Paired reads can yield evidence for genomic “structural events”, such as deletions, translocations, and inversions.
- Alignment coloring options help highlight these events based on:
 - Inferred insert size (template length)
 - Pair orientation (relative strand of pair)

Paired-end sequencing


DNA or
cDNA




Fragment and
size select



Paired-end sequencing



Paired-end sequencing



Interpreting inferred insert size

The “inferred insert size” can be used to detect structural variants including

- Deletions
- Insertions
- Inter-chromosomal rearrangements: (Undefined insert size)

Deletion


What is the effect of a deletion on inferred insert size?

Deletion

Reference
Genome



Subject



Deletion

Reference
Genome



Subject




Deletion

Reference
Genome



Subject



Deletion

Inferred insert size is $>$ expected value

Reference
Genome




inferred insert size

Subject



expected insert size

Color by insert size




The screenshot displays a genome browser interface with several tracks. The top track is labeled 'NA12878.bwa.sort.rmdup.realign.am Coverage' and shows a coverage plot with a range of [0 - 61]. Below it are alignment tracks for 'NA12878.bwa.sort.rmdup.realign.am', 'NA12891.bwa.sort.rmdup.realign.am Coverage', 'NA12891.bwa.sort.rmdup.realign.am', and 'NA12892.bwa.sort.rmdup.realign.am Coverage'. A context menu is open over the 'NA12878.bwa.sort.rmdup.realign.am' track, showing options for 'Color alignments by'. The 'insert size' option is selected and highlighted in dark grey.

Context menu options for 'Color alignments by':



- no color
- insert size
- pair orientation
- insert size and pair orientation
- read strand
- first-of-pair strand
- read group
- sample
- tag
- bisulfite mode

Deletion




Pairs with larger than expected insert size are colored red.


Insert size color scheme

- Smaller than expected insert size: 
- Larger than expected insert size: 
- Pairs on different chromosomes


Each end colored by chromosome of its mate



Rearrangement



Rearrangement



Interpreting Read-Pair Orientations

Orientation of paired reads can reveal structural events:

- Inversions
- Duplications
- Translocations
- Complex rearrangements

Orientation is defined in terms of

- read strand, left *vs* right, *and*
- read order, first *vs* second

Inversion

Reference
genome



Inversion

Reference
genome




Inversion

Reference
Genome



Subject



Inversion


Reference
Genome




Subject



Inversion



Inversion




Inversion


Reference
Genome




Subject



Inversion




Inversion




Inversion

Reference
Genome




Inversion



Anomaly: expected orientation of pair is inward facing ($\longrightarrow \longleftarrow$)


Inversion



“Left” side pair


Inversion

Reference
Genome



“Right” side pair

Color by pair orientation




The image shows a screenshot of a genome browser interface. A context menu is open over a track labeled 'NA12878.bwa.sort.rmdup.realign.bam'. The menu options are:


- Rename Track...
- Copy read details to clipboard
- Group alignments by
- Sort alignments by
- Color alignments by**
 - no color
 - insert size
 - pair orientation**
 - insert size and pair orientation
 - read strand
 - first-of-pair strand
 - read group
 - sample
 - tag
 - bisulfite mode
- ✓ Shade base by quality
- ✓ Show mismatched bases
- Show all bases
- View as pairs
- Go to mate
- View mate region in split screen
- Set insert size options ...

The background shows a coverage plot and alignment tracks for tracks labeled 'NA12878.bwa.sort.rmdup.realign.bam', 'NA12891.bwa.sort.rmdup.realign.bam', and 'NA12892.bwa.sort.rmdup.realign.bam'. The alignment tracks show reads with various colors and orientations, indicating different pair orientations.

Inversion



Interpretation of read pair orientations



- LR Normal reads.
The reads are left and right (respectively) of the unsequenced part of the sequenced DNA fragment when aligned back to the reference genome.
- LL,RR Implies inversion in sequenced DNA with respect to reference.
- RL Implies duplication or translocation with respect to reference.

These categories only apply to reads where both mates map to the same chromosome.

Figure courtesy of Bob Handsaker

IGV hands-on tutorial

[https://github.com/griffithlab/
rnaseq_tutorial/wiki/IGV-Tutorial](https://github.com/griffithlab/rnaseq_tutorial/wiki/IGV-Tutorial)

We are on a Coffee Break & Networking Session

